



# Heavy Cut H8.02

## Coarse polishing compound, silicone-oil-free

Innovative machine polish for fast reworking of heavily weathered paintwork, elimination of deep scratches, and effective removal of paint mists and sanding traces of up to 1,500 grain. With its extremely homogeneous abrasive grain, Heavy Cut 8.02 achieves an extremely high level of cut with an excellent gloss level. Can be polished for prolonged periods without sticking and with low dust formation. Ideally suited to all types of paint (both soft and scratch-proof). With Daimler approval. Cut: 8,5. Gloss: 5,0

page 1 of 1

### Areas of use

Paintwork of cars, commercial vehicles, motor cycles, etc

### Recommendations for use

Apply in a crosswise motion with a rotary polisher and a lambskin pad (for sanding traces of 1,500–2,500) or a polishing pad (for sanding traces of 2,500–5,000). Apply polishing compound at medium speed and with medium pressure. Polish afterwards with Hochglanz-Antihologramm-Politur for the best possible finish.

### Container

Container	Item no.
1 L	312001
0,25 L	312250

### Warnings

Shake before using.;Protect against frost and excessive heat.;Do not use on hot surfaces.;Before using, check suitability and compatibility.;

### Notice

This product information can advice you only without obligation. Liability on our part can not be derived.Please check whether the product is suitable for your application. We will be pleased to assist you.